



Physical:
Housing: NY,UL 94V-0
Contact: Copper Alloy

Specifications:
Voltage Current Rating: 1A,30V AC
Insulation Resistance: 1000M ohn min
Contact Resistance: 30m ohn max
Dielectric Withstanding Voltage:
AC 500V for 1 Minute
temperature Rating: -55°C~+105°C

REV.	ECN. NO.	DATE
1.X	RELEASED	09/02/06

P 120 N X X XXX X X
MCA SERIES
NO OF PINS
INSULATOR
N: NYLON66
C: PCT
S: PPS
B: PBT
CONTACT
B: BRASS
P: PH,BRONZE
CONTACT THICKNESS
3: 0.3MM
COLOR
W: WHITE
B: BLACK
P: POST WITHOUT RIB
Q: POST WITH RIB
C: CLIP
E: WITH EAR
F: STRADDLE WITH EAR
N: NO POST, NO STANDOFF
PLATING CODE
01: GOLD FLASH
:
TAIL LENGTH
2: 2.54 MM
3: 3.00 MM
4: 3.56 MM
5: STRADDLE Y2 TYPE
6: STRADDLE Y1 TYPE
7: SMT TYPE



崧嵐企業有限公司

TOWNES ENTERPRISE CO.,LTD

INTENDED USE:		TITLE / PRAT NO.:	
X: ±0.25	X*: ±0.0°	CUSTOMER DRAWING / P120NXXXXXXXX	
.XX: ±0.13	.X*: ±2.0°	DWG. NO.: 20060901-83(FY)	
.XXX: ±0.08	.XX*: ±1.0°	SCALE: 1:1	
MATL.:	CHKD.:	PAGE: 1/1	
FINISH:		REV.: 1.0	

TOP VIEW
PCB LAYOUT RECOMMENDED